

Description	Gigabit Ethernet PCIe x1, DS	
Order number	S26361-F3067-E60/ -L60	
Part number	D2907	
Supplier	FSC	
short description	PCI express x1 card for 10/100/1000 Mbit/s LAN connection; manageability for AMD platforms	Dash
Physical specifications		
Dimension (W x D x H in mm)		
complete fitting	-	
card	66 mm x 62,5 mm	
cable length	-	
Weight	50 g	
external device	-	
Internal device	x	
Full height slot	x (depending on system form factor)	
low profile slot	x (depending on system form factor)	
3,5" bay	-	
5,25" bay	-	
others	-	
Interfaces		
on component external	RJ45	
on component internal	-	
Package contents		
driver	for optional deliveries on DVD	
adapter	-	
manuals	for optional deliveries on DVD	
cable	-	
others	-	
Electrical power consumption		
supply voltage	3,3V, 12V, 3,3VAUX from host	
power consumption	600mA, 10mA, 375mA max = 2 W	
Driver support		
Windows 2000	-	
Windows NT4	x	
Windows XP	x	
Windows Vista	x	
Linux	x	
others	DOS; Netware	
System requirements		
Interfaces	1 free internal PCI express slot	
others	-	
Approvals/Certifications		
CE certification	x	
according to EU Directives 89/336/EEC (EMC) and 06/95/EC (Product safety)	According to EU Directives 2004/108/EC (EMC) and 2006/95/EC (Product safety)	
Ergonomics	-	
ISO9241 (GS mark)		
Product safety	x	
IEC60950, EN60950, UL 60950, CSA22.2, UL 60950, CSA22.2, No.60950	IEC 60950-1, EN 650950-1, UL 60950-1, CSA C22.2 No. 60950-1	
Electromagn. compatibility	x	
EN55022/B, FCC class B, EN55024, EN61000-3-2/3	EN55022/B, FCC class B, EN55024	
additional	-	
Environmental compatibility		
RoHS (Restriction of hazardous substances)	x	
WEEE (Waste electrical and electronical equipment)	x	
others	-	
Norms and Standards	IEEE 802.3ab; IEEE 802.3u; IEEE 802.3x; PCI express 1.1; WHQL	
Ambient temperature (IEC 721)	15°C- 35°C	
Security	-	

Technical Specification	
	Bus Interface: Broadcom BCM5761; PCI express Rev. 1.1; USB interface required only for DASH Network Interface: Gigabit Ethernet over CAT5 1000Base-T Ethernet 10Base-T and Fast Ethernet 100Base-T RJ-45 connector Auto-Negotiation, Full Duplex and Half Duplex support Notes: Remote Boot PXE ACPI Wake on LAN support DASH support together with selected mainboards
Picture	

